

# MATERIAL SAFETY DATA SHEET

## Chemical Product

Product Name: ETHANOLAMINE (Mono)

CAS#: 141-43-5

Synonym: Colamine, Glycinol, Olamine; Ethanolamine; 2-Aminoethanol; 2-Hydroxyethylamine; beta-Ethanolamine; beta-Hydroxyethylamine

Chemical Name: Ethanolamine (Mono)

Chemical Formula: HOCH<sub>2</sub>CH<sub>2</sub>NH<sub>2</sub> or C<sub>2</sub>H<sub>7</sub>NO

## Composition and Information on Ingredients

Name	S.K.U	% by Weight
ETHANOLAMINE (Mono)	GCS-6382	100

## Hazards Identification

Potential Acute Health Effects:

Very hazardous in case of eye contact (irritant), of ingestion,. Hazardous in case of skin contact (irritant, permeator), of inhalation (lung irritant). Slightly hazardous in case of skin contact (corrosive), of eye contact (corrosive). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath.

Inflammation of the eye is characterized by redness, watering, and itching.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available.

TERATOGENIC

EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to kidneys, lungs, liver, and central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection..

## First Aid Measures

**Eye Contact:**

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Get medical attention immediately. Finish by rinsing thoroughly with running water to avoid a possible infection.

**Skin Contact:**

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

**Serious Skin Contact:**

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.

**Inhalation:**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Serious Inhalation:**

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. **WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

**Ingestion:**

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Serious Ingestion: Not available

## **Fire and Explosion Data**

Flammability of the Product: Combustible.

Auto-Ignition Temperature: 410°C (770°F)

Flash Points: CLOSED CUP: 86°C (186.8°F). OPEN CUP: 93.34°C (200°F) (Cleveland).

Flammable Limits: LOWER: 3% UPPER: 23.5%

Products of Combustion: These products are carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO, NO<sub>2</sub>...).

**Fire Hazards in Presence of Various Substances:**

Flammable in presence of open flames and sparks, of heat. Non-flammable in presence of shocks.

**Explosion Hazards in Presence of Various Substances:**

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

**Fire Fighting Media and Instructions:**

SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Not available.

## **Accidental Release Measures**

**Small Spill:**

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. If necessary: Neutralize the residue with a dilute solution of acetic acid.

**Large Spill:**

Combustible material. Corrosive liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Neutralize the residue with a dilute solution of acetic acid. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities

## **Handling and Storage**

**Precautions:**

Keep container dry. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, acids.

**Storage:**

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Sensitive to light. Store in light-resistant containers. Hygroscopic

## Exposure Controls/Personal Protection

### Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection: Safety glasses. Lab coat.

### Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

### Exposure Limits:

TWA: 3 STEL: 5 (ppm) [United Kingdom (UK)] TWA: 3 STEL: 6 (ppm) from ACGIH (TLV) [United States] STEL: 15 (mg/m<sup>3</sup>) from NIOSH [United States] TWA: 3 STEL: 6 (ppm) from NIOSH [United States] TWA: 3 (ppm) from OSHA (PEL) [United States] TWA: 6 (mg/m<sup>3</sup>) from OSHA (PEL) [United States] Consult local authorities for acceptable exposure limits.

## Physical and Chemical Properties

Physical state and appearance : Liquid. (Viscous liquid.)

Odor : Ammoniacal. Fish. Unpleasant.

Taste : Not available.

Molecular Weight : 61.08 g/mole

Color : Colorless. Clear

pH (1% soln/water) : 10 [Basic.]

Boiling Point : 170.8°C (339.4°F)

Melting Point : 10.3°C (50.5°F)

Critical Temperature : 341°C (645.8°F)

Specific Gravity : 1.018 (Water = 1)

Vapor Pressure : 0.1 kPa (@ 20°C)

Vapor Density : 2.1 (Air = 1)

Volatility : Not available.

Odor Threshold : Not available.

Water/Oil Dist. Coeff. : The product is more soluble in water; log(oil/water) = -1.3

Ionicity (in Water) : Not available.

Dispersion Properties : See solubility in water, methanol, diethyl ether, and acetone. Solubility : Soluble in cold water, hot water, methanol, and acetone. Partially soluble in diethyl ether. Solubility in Benzene @ 25 deg. C: 1.4% Solubility in Ether: 2.1% Solubility in Carbon Tetrachloride: 0.2% Solubility in Heptane: <0.1% Miscible with Chloroform, Glycerin. Immiscible with fixed oils, solvent Hexane. Slightly soluble in Petroleum Ether.

## Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Heat, ignition sources, incompatible materials, light, moisture.

Incompatibility with various substances: Reactive with oxidizing agents, acids.

Corrosivity: Highly corrosive in presence of aluminum, of copper.

Special Remarks on Reactivity:

Hygroscopic; keep container tightly closed. Sensitive to light. INCOMPATIBLE WITH: ACETIC ACID, ACETIC ANHYDRIDE, ACROLEIN, ACRYLIC ACID, ACRYLONITRILE, CHLOROSULFONIC ACID, EPICHLOROHYDRIN, HYDROCHLORIC ACID, HYDROFLUORIC ACID, MESITYL OXIDE, NITRIC ACID, OLEUM, PROPIOLACTONE (BETA-), SULFURIC ACID, VINYL ACETATE, HALOGENS.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

## Toxicological Information

Routes of Entry: Absorbed through skin. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

Acute oral toxicity (LD50): 700 mg/kg [Mouse]. Acute dermal toxicity (LD50): 1000 mg/kg [Rabbit].

Chronic Effects on Humans:

May cause damage to the following organs: kidneys, lungs, liver, central nervous system (CNS).

Other Toxic Effects on Humans:

Very hazardous in case of ingestion, . Hazardous in case of skin contact (irritant, permeator), of inhalation (lung irritant). Slightly hazardous in case of skin contact (corrosive), of eye contact (corrosive).

Special Remarks on Toxicity to Animals: Not Available.

Special Remarks on Chronic Effects on Humans:

May cause adverse reproductive effects and birth defects (teratogenic) based on animal test data. May affect genetic material (mutagenic)

**Special Remarks on other Toxic Effects on Humans:**

Acute Potential Health Effects: Skin: Causes moderate skin irritation and possible burns. It can be absorbed through the skin. It may be harmful if absorbed through the skin. Eyes: Causes severe eye irritation and possible eye burns. Inhalation: Causes respiratory tract irritation. May cause shortness of breath and an asthma-like condition. It may also affect behavior/central nervous system (nausea, headache, weakness, dizziness, giddiness, sleepiness, loss of coordination and judgment) Ingestion: May be harmful if swallowed. Causes gastrointestinal tract irritation with nausea.

Toxicological Data on Ingredients: Ethanolamine: ORAL (LD50): Acute: 1720 mg/kg [Rat.]. 700 mg/kg [Mouse]. DERMAL (LD50): Acute: 1000 mg/kg [Rabbit].

## **Ecological Information**

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation: Not available.

## **Disposal Considerations**

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

## **Transformation Information**

Land transport (ADR-RID)

Proper shipping name: ETHANOLAMINE or ETHANOLAMINE SOLUTION

UN N°: 2491

H.I. nr: 80

ADR - Class: 8

Labelling - Transport: 8 : Corrosive substance.

ADR - Group: III

Sea transport (IMDG) [English only]

Proper shipping name: ETHANOLAMINE or ETHANOLAMINE SOLUTION

UN N°: 2491

IMO-IMDG - Class or division: 8 : Corrosive substance.

IMO-IMDG - Packing group: III

Air transport (ICAO-IATA) [English only]

Proper shipping name: ETHANOLAMINE or ETHANOLAMINE SOLUTION

UN N°: 2491

IATA - Class or division: 8 : Corrosive substance.

IATA - Packing group: III

## Other Regulatory Information

Federal and State Regulations:

Connecticut hazardous material survey.: Ethanolamine Illinois toxic substances disclosure to employee act: Ethanolamine Rhode Island RTK hazardous substances: Ethanolamine Pennsylvania RTK: Ethanolamine Minnesota: Ethanolamine Massachusetts RTK: Ethanolamine Massachusetts spill list: Ethanolamine New Jersey: Ethanolamine TSCA 8(b) inventory: Ethanolamine

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada): CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F). CLASS E: Corrosive liquid.

DSCL (EEC): R20- Harmful by inhalation. R36/37/38- Irritating to eyes, respiratory system and skin. S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28- After contact with skin, wash immediately with plenty of water.

S36/37/39- Wear suitable protective clothing, gloves and eye/face protection. S46- If swallowed, seek medical advice immediately and show this container or label.

### HMIS (U.S.A.):

Health Hazard: 2

Fire Hazard: 1

Reactivity: 0

**Personal Protection: E**

National Fire Protection Association (U.S.A.):

**Health: 2**

Flammability: 1

**Reactivity: 0**

Specific hazard:

**Protective Equipment:**

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

**Additional Information**



References: Not available.

Other Special Considerations: Not available.

***Disclaimer:***

\*\*\*\*\*

The information contained herein in good faith but makes no representations as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

 **makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly,  will not be responsible for damages resulting from use of or reliance upon this information.**